

M0150099 | M0200099 | M0250099 SERIES

DATASHEET

Una batería portátil para cualquier necesidad.



199















SPECIFICATIONS

Model	MO 1500 ⁹⁹	MO 2000 ⁹⁹	MO 2500 ⁹⁹	
Rated Power	1500VA	2000VA	2500VA	
Peak Power	3000VA	4000VA	5000VA	
Dimensions	530mm (20.9 in)X320mm (12.6 in)X430mm (16.9 in)			
Weight	34 kg (75 lbs)	36 kg (79 lbs)	41 kg (90 lbs)	
Battery Type	LiFePO ₄			
Battery Capacity	2048Wh, 80Ah(25.6V)		2688Wh, 105Ah (25.6V)	
Battery Cycle Life	>4000 cycles 50% - >2000 clyces 90%			



OUTPUT

AC Output	Output Waveform	Pure-Sine Wave, THD<3%	
	Rated Voltage	100/110/120/220/230/240V	
	Rated Frequency	60/50Hz	
DC Output	Cigarette Lighter	12V/10A	
	5.5mm/6mm Port	12V/6A	
	USB	5V/3.1A, QC3.0	
	TYPE C	PD60W	

CHARGING INPUT

	Model	MO 1500 ⁹⁹	MO 2000 ⁹⁹	MO 2500 ⁹⁹
AC	Wall Outlet	100~120V / 200~240V, Max. 300W, 6 hours fully charged	100~120V / 200~240V, Max. 300W, 6 hours fully charged	100~120V / 200~240V, Max. 300W, 9 hours fully charged
Solar	MPPT Control System	36~140v, Max. 800W, 2.5 hours fully charged	36~140v, Max. 800W, 2.5 hours fully charged	36~140v, Max. 900W, 2.5 hours fully charged
Car	8mm Port	12~15V / 24~30V, Max. 160W, 18 hours fully charged	12~15V / 24~30V, Max. 160W, 18 hours fully charged	12~15V / 24~30V, Max. 160W, 24 hours fully charged
Wind (1)	3AC Port	3AC 22~26V, Max. 600W, 3.4 hours fully charged	3AC 22~26V, Max. 600W, 3.4 hours fully charged	3AC 22~26V, Max. 600W, 4.5 hours fully charged
DC Quik	Anderson SB50	24~28V, Max, 2000W, 1.5 hours fully charged	24~28V, Max, 2000W, 1.5 hours fully charged	24~28V, Max, 2500W, 1.5hours fully charged